

SC1325CS 产品单页

SC1325CS Product Flyer

- 基于思特威SmartClarity®-3技术平台打造的消费电子应用CMOS图像传感器升级新品
Upgraded CMOS image sensor for consumer electronics cameras, built on SmartSens' SmartClarity®-3 technology platform
- 搭载SFCPixel®专利技术
Embedded SFCPixel® technology
- 具备高感度、低功耗等优势
High sensitivity and low power consumption
- 高温性能、高动态范围、满阱容量(FWC)等关键性能实现全面优化
Fully optimized high temperature performance, high dynamic range, and full well capacity



公司简介 | Company Profile

思特威(上海)电子科技股份有限公司 SmartSens Technology (股票简称:思特威, 股票代码:688213)是一家从事CMOS图像传感器芯片产品研发、设计和销售的高新技术企业,总部设立于中国上海,在多个城市及国家设有研发中心。

自成立以来,思特威始终专注于高端成像技术的创新与研发,凭借自身性能优势得到了众多客户的认可和青睐。作为致力于提供多场景应用、全性能覆盖的CMOS图像传感器产品企业,公司产品已覆盖了安防监控、机器视觉、智能车载电子、智能手机等多场景应用领域的全性能需求。

思特威将秉持“以前沿智能成像技术,让人们更好地看到和认知世界”的愿景,以客户需求为核心动力,持续推动前沿成像技术升级,拓展产品应用领域,与合作伙伴一起助推未来智能影像技术的深化发展。

SmartSens Technology (Shanghai) Co., Ltd. (Stock Code:688213) is a high-performance CMOS image sensor (CIS) chip design company. It is headquartered in Shanghai and has research centers in many cities around the world.

SmartSens has been dedicated to pushing forward the frontier of imaging technology and growing in popularity among customers since it was established. SmartSens' CMOS image sensors provide advanced imaging solutions for a broad range of areas such as surveillance, machine vision, automotive and cellphone cameras.

SmartSens is committed to continuous innovation of products and fueling growth in numerous industries by delivering a more comprehensive portfolio of image sensors.

SmartClarity®-3 Series

规格说明 | Specifications

项目 Item	参数 Parameters
Resolution	13MP
Pixel Array	4224H x 3136V
Pixel Size	1.12μm× 1.12μm
Optical Format	1/3.06"
Max Frame Rate	4208H × 3120V @30fps 10bit
Output Interface	10/8-bit 1/2/4Lane MIPI
Output Format	RAW RGB
CRA	33.69°
Sensitivity	5006 e-/lux*s
Dynamic Range	74.19dB
SNR	37.3dB
Operation Temperature Range	-20°C ~ +85°C
Best IQ Temperature	0°C ~ +60°C
Power Supply	AVDD = 2.8V
	DVDD = 1.2V
	DOVDD = 1.8V/1.2V
Package	COB/RW
Package Size	COB: 5.360mm × 4.710mm, 48-pin
	RW: 5.410mm × 4.760mm, 48-pin
ESD Rating	HBM: Class 3A
	CDM: Class C3

产品特性 | Features

- 高温性能优化, 增强低功耗实感
Optimized high-temperature performance and low power performance
- 高动态与高感度, 显著提升画质表现
High dynamic range and high sensitivity, delivering clear improvements in image quality
- Sparse PDAF®相位检测对焦技术, 升级支持 Type 2 输出模式
Sparse PDAF® phase detection autofocus with Type-2 output mode available
- 灵活适配智能手机后置主摄、后置超广角及前摄
Supports rear main, rear ultra-wide-angle, and front cameras for smartphone applications

应用场景 | Applications

- 智能手机后置主摄 / 后置超广角 / 前摄
Rear main camera / rear ultra-wide-angle / front camera for smartphone applications
- 智能家用摄像头
Smart home cameras
- 可视门铃应用
Video doorbell applications
- 可移动设备相机
Mobile device cameras
- 视频电话会议设备
Video conferencing systems
- 电池供电式摄像头
Battery-powered cameras



WeChat



LinkedIn

Website	www.smartsensotech.com
安防监控类应用	security@smartsensotech.com
车载电子类应用	automotive@smartsensotech.com
工业及机器视觉	machinevision@smartsensotech.com
智能手机类应用	mobile_cs@smartsensotech.com
其他	cs@smartsensotech.com

- 上海办公室
上海市闵行区田林路889号科技绿洲四期8号楼
Building 8, Shanghai Business Park IV, No. 889 Tianlin Road,
Minhang District, Shanghai
Tel: 021-6485-3570
- 深圳办公室
深圳市龙岗区坂田街道雅宝路1号 星河WORLD B座2801室
B2801, Building B, Galaxy WORLD, No.1 Yabao Road,
Bantian Street, Longgang District, Shenzhen
Tel: 0755-2373-9713

- 合肥办公室
合肥市经济技术开发区宿松路3963号智能科技园E栋1501室
Rm 1501, Bldg E, Intelligent Technology Park, No. 3963 Susong Road,
Economic and Technological Development District, Hefei
- 香港办公室
香港观塘鸿图道21号讯科中心10楼F室
RM F, 10/F, INFOTECH CENTRE, 21 HUNG TO RD
- 美国 (圣克拉拉)
4633 Old Ironsides Dr. Ste330 Santa Clara, CA 95054
Tel: +1 408 981 6626